Rasaplast Non-Cementitious Basecoat

SEC. 07240
Submittal Sheet

Description:

- Decoplast Rasaplast Base Coat / Adhesive is a ready mixed 100% acrylic non-cementitious embedding basecoat .
- Decoplast Rasaplast Basecoat is applied with a standard stainless steel trowel.
- Decoplast Rasaplast Base Coat has been designed to be an embedding coat for applying Decoplast EPS Foam to approved substrates.

Preparation:

- The surface should be clean and free of any contaminates.
- Surface and air temperature will be at a minimum of 45°F during and at least, 24 hours after the application.

Mixing:

- Using a Goldblatt Jiffy Mixer, or equivalent, blend the Rasaplast to a uniform consistency. Remember: **DO NOT ADD WATER**.

Application:

Base / Embedding Coat

- Using a stainless steel trowel apply the base coat to a uniform thickness of 1/8".
- Working in 40" strips, immediately embed with the trowel the fiberglass reinforcing mesh into the Rasaplast making sure that no mesh is visible when done.
- Double-wrap the corners and overlap not less than 3" at mesh joints.
- Continue until the entire field is complete.

Greenmaker INDUSTRIES
"Solutions without compromise"

697 Oakwood Avenue, West Hartford, CT 06110
voice: 860-761-2830 fax: 860.761.2831
www.decoplast.com

Rasaplast Non-Cementitious Basecoat

SEC. 07240
Submittal Sheet

Cleaning:

- Clean equipment and containers with water as quickly as possible after use.

Limitations:

- Protect the material from freezing.
- Finishes must be applied at or above 45°F
- Do not apply on damp surfaces or when rain is forecasted.
- Consult the manufacturer's Material Safety Data Sheets.
- Store Decoplast materials in a cool, dry place.
- Protect from freezing and direct sunlight.
- Store at no less than 4°C (40°F)

Coverage:

- Each 5 Gallon pail has an approximate coverage of 150-200 square feet.

Drying Time:

- Recommended drying time for Rasaplast is approximately 24 hours. The estimate is based on optimum weather conditions of 70°F, with 55% relative humidity.
- Drying times will vary based on temperature and humidity.

Availability:

- Decoplast Rasaplast Base Coat is available only at authorized Decoplast distributors.

Warranty:

- Consult your nearest Decoplast professional for details.

Disclaimer
Greenmaker Industries will not be held liable for incidental and consequential damages, directly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.

Greenmaker INDUSTRIES
"Solutions without compromise"
697 Oakwood Avenue, West Hartford, CT 06110
voice: 860-761-2830 fax: 860.761.2831
www.decoplast.com