keep a **SharpEye**™ *on your safety*

40/40M | **40/40I** | 40/40L-LB | 40/40UFL | 40/40L4-L4B | 40/40U-UB | 40/40R

40/40I

Triple IR (IR3) Flame Detector

Superior performance, reliability and immunity to false alarms

SharpEye™

The new 40/40I, a multi spectrum based on three IR bands (IR3), detects fuel and gas fires at long distances with the highest immunity to false alarms. The 40/40I IR3 can detect a 1 ft² (0.1m²) gasoline pan fire at 215 ft (65m) in less than 5 seconds.

The 40/40I is the most durable and weather resistant flame detector currently on the market. Its new features include a heated window, to eliminate condensation and icing; HART capabilities for digital communications; lower power requirements; and a compact, lighter design.

Due to increased reliability, the 40/40 Series warranty period has been extended to 5 years and is SIL2 (TUV) approved to IEC 61508.

FEATURES & BENEFITS

- Multi spectrum design - for long distance detection and high false alarm immunity
- Sensitivity selection - to ensure no zone crossover detection
- Automatic and Manual Built-In-Test (BIT) - to assure continued reliable operation
- Heated window - for operation in harsh weather conditions (snow, ice, condensation)
- Multiple output options for maximum flexibility and compatibility
  - Relays (3) for Alarm, Fault and Auxiliary
  - 0-20mA (stepped)
  - HART Protocol for maintenance and asset management
  - RS-485, Modbus Compatible
- High Reliability - MTBF - minimum 150,000 hours
- Approved to Safety Integrity Level 2 (SIL2 – TUV)
- 5-Year Warranty
- User Programmable via HART or RS-485
- Ex approved for Zone 1 hazardous area location
  - ATEX
  - IECEx
  - FM/FMC- CSA
- 3rd party performance tested
  - EN54-10 (VdS)
  - FM3260 (FM)
  - DNV Marine Approval

APPLICATIONS

Offshore Oil & Gas installations
Onshore Oil & Gas installations and pipelines
Chemical plants
Petrochemicals plants
Storage Tank farms
Aircraft hangars
Power Generation facilities
Pharmaceutical Industry
Printing Industry
Warehouses
Automotive
Explosives & Munitions
Waste Disposal facilities

Headquarters: 218 Little Falls Road | Cedar Grove | NJ 07009 | USA
Tel: +1 (973) 239-8398 | +1 (800) 452-2107 (US only) | Fax: +1 (973) 239-7614
Houston: +1 (832) 321-5229 | Europe: +44 (141) 578-0693
E-mail: spectrex@spectrex.net | www.spectrex.net

SPECTREX INC.

keep a SharpEye™ on your safety

GENERAL SPECIFICATIONS

Spectral Response	Three IR Bands
Detection Range (at highest Sensitivity Setting for 1ft² (0.1m²) pan fire)	

Fuel	ft / m	Fuel	ft / m	Fuel	ft / m
n-Heptane	215 / 65	Kerosene	150 / 45	Methane*	100 / 30
Gasoline	215 / 65	Ethanol 95%	135 / 40	LPG*	100 / 30
Diesel Fuel	150 / 45	Methanol	115 / 35	Polypropylene Pellets	16 / 5
JP5	150 / 45	IPA (Isopropyl Alcohol)	135 / 40	Office Paper	33 / 10

* 20" (0.5m) high, 8" (0.2m) width plume fire

Response Time	Typically 5 seconds
Adjustable Time Delay	Up to 30 seconds
Sensitivity Ranges	4 Sensitive ranges for 1 ft² (0.1m²) n-heptane pan fire from 50 ft (15m) to 215 ft (65m)
Field of View	Horizontal 100°; Vertical 95°
Built-in-Test (BIT)	Automatic (and Manual)
Temperature Range	Operating: -67°F to +167°F (-55°C to +75°C) Option: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
Humidity	Up to 95% non-condensing (withstands up to 100% RH for short periods)
Heated Optics	To eliminate condensation and icing on the window

ELECTRICAL SPECIFICATIONS

Operating Voltage	24 VDC nominal (18-32 VDC)
Power Consumption	Standby: Max. 90mA (110mA with heated window) Alarm: Max. 130mA (160mA with heated window)
Cable Entries	2 x 3/4" - 14NPT conduits or 2 x M25 x 1.5 mm ISO
Wiring	12 - 22AWG (2.5mm² - 0.3mm²)
Electrical Input Protection	According to MIL-STD-1275B
Electromagnetic Compatibility	EMI/RFI protected to EN61326-3 and EN61000-6-3
Electrical Interface	The detector includes twelve (12) terminals with five (5) wiring options (factory set)

OUTPUTS

Relays	Alarm, Fault and Auxiliary SPST volt-free contacts rated 5A at 30 VDC or 250 VAC.
0-20mA (stepped)	Sink (source option) configuration Fault: 0 +1mA Warning: 16mA ± 5% BIT Fault: 2mA ± 10% Alarm: 20mA ± 5% Normal: 4mA ± 10% Resistance Loop: 100-600 Ω
HART Protocol	Optional HART communications on the 0-20mA analog current (FSK) - used for maintenance, configuration changes and asset management, available in mA source output wiring options
RS-485	RS-485 Modbus compatible communication link that can be used in computer controlled installations

MECHANICAL SPECIFICATIONS

Materials	- Stainless Steel 316L with electro polish finish
Enclosure options	- Heavy duty copper free aluminum (less than 1%), red epoxy enamel finish
Mounting	Stainless Steel 316L with electro polish finish
Dimensions	Detector 4" x 4.6" x 6.18" (101.6 x 117 x 157 mm)
Weight	Detector (St.St.) 6.1 lb (2.8 kg) Tilt mount 2.2 lb (1.0 kg) Detector, aluminum 2.8 lb (1.3 kg)
Environmental Standards	Meets MIL-STD-810C for Humidity, Salt & Fog, Vibration, Mechanical Shock, High Temp, Low Temp
Water and Dust	IP66 and IP67 per EN60529, NEMA 250 6P

APPROVALS

Hazardous Area	ATEX and IECEx	Ex II 2 GD, Ex de IIC T5 (-55°C to +75°C) Ex tD A21 IP66/X7 T 95°C	 Ex de IIC T4 (-55°C to +85°C) Ex tD A21 IP66/X7 T 105°C
	FM/FMC/CSA	Class I Div. 1, Groups B, C & D Class II/III Div. 1, Groups E, F & G	
Performance	EN54-10 (VdS) FM-3260 (FM) DNV Marine Approval		
Reliability	IEC61508 - SIL2 (TUV)		

ACCESSORIES

Fire Simulator	20/20-310	**U-Bolt/Pole Mount**	789260-2 (2" pole)	**Mini Laptop Kit**	777820	**Laser Pointer**	777166
Tilt Mount	40/40-001		789260-1 (3" pole)	**Weather Protector**	777163	(Detector area coverage)	
Duct Mount	777670	**USB RS485 Harness Kit**	794079-5	**Air Shield**	777650		

Specifications subject to change

For more information view manual or website www.spectrex.net

SPECTREX INC.